



www.hwlok.com



DIN 5510-2
Preventive Fire Protection
in Railway vehicles




80 ~ 778 N
8.2 ~ 79.3Kgf
18 ~ 175 lbf



COLD WEATHER CABLE TIES

Operating
Temperature





Min. Installation
Temperature



COLD WEATHER CABLE TIES

- Multi-function cable ties are available in countless applications.
- Special nylon raw material can be exposed to zero temperatures for a long time.
- Impact resistant and UV resistant
- Compliance with UL Recognized
- Compliance with DIN5510-2 (Preventive Fire Protection in Railway vehicles)
- Material: PA6,6 cold weather resistant
- Color: Black



Part No.	Length (L) mm (inch)	Width (W) mm (inch)	Max.Bundle ø mm (inch)	Min. Loop Tensile Strength			Recommended Tensioning Tools
				N	kgf	lbf	
GT-80M-WELB	80 (3.15)	2.4 (0.09)	15 (0.59)	80	8.2	18	 GIT-703
GT-100M-WELB	100 (3.94)	2.5 (0.10)	22 (0.87)	80	8.2	18	
GT-150M-WELB	150 (5.91)	2.5 (0.10)	35 (1.38)	80	8.2	18	
GT-150I-WELB	150 (5.91)	3.6 (0.14)	35 (1.38)	178	18.2	40	
GT-200I-WELB	200 (7.87)	3.6 (0.14)	53 (2.09)	178	18.2	40	
GT-250I-WELB	250 (9.84)	3.6 (0.14)	65 (2.56)	178	18.2	40	
GT-300I-WELB	300 (11.81)	3.6 (0.14)	76 (2.99)	178	18.2	40	
GT-200ST-WELB	200 (7.87)	4.8 (0.19)	50 (1.97)	222	22.6	50	
GT-250ST-WELB	250 (9.84)	4.8 (0.19)	60 (2.36)	222	22.6	50	
GT-300ST-WELB	300 (11.81)	4.8 (0.19)	76 (2.99)	222	22.6	50	
GT-300HD-WELB	300 (11.81)	7.6 (0.30)	76 (2.99)	534	54.5	120	 GIT-704G
GT-370HD-WELB	370 (14.57)	7.6 (0.30)	102 (40.2)	534	54.5	120	
GT-540HD-S-WELB	533 (20.98)	7.6 (0.30)	140 (5.51)	534	54.5	120	
GT-750HD-S-WELB	750 (29.53)	7.6 (0.30)	218 (8.59)	534	54.5	120	
GT-530HD-WELB	530 (20.87)	9.0 (0.35)	140 (5.51)	778	79.3	175	
GT-630HD-WELB	609 (23.98)	9.0 (0.35)	178 (7.01)	778	79.3	175	

