



BEAD TIES

- Reusable, easy to install and release
- Material: Polyamide 6,6, UL94V-2
- Color: All colors are available


GTB-100





GTB-310



GTB-320



GTMB-90



Part No.	Length (L) mm (inch)	Width (W) mm (inch)	Max.Bundle ø mm (inch)	Min. Loop Tensile Strength			Mounting Hole ø mm (inch)	Panel Thickness mm (inch)
				N	kgf	lbf		
GTB-100	107 (4.21)	2.3 (0.09)	29 (1.14)	40	4.1	9	--	--
GTB-310	316 (12.44)	4.4 (0.17)	80 (3.15)	311	31.8	70		
GTB-320	322 (12.68)	4.4 (0.17)	90 (3.54)	40	4.1	9	--	--
GTMB-90	93 (3.66)	2.4 (0.09)	25 (0.98)	40	4.1	9	3.0 (0.12)	1.6 (0.06)

STOP TIES

- Tie knuckle will prevent tightening on the object, forming a loop for sorting application
- Material: Polyamide 6,6, UL94V-2
- Color: All colors are available



Part No.	Length (L) mm (inch)	Width (W) mm (inch)	Min.Bundle ø mm (inch)	Max.Bundle ø mm (inch)	Min. Loop Tensile Strength		
					N	kgf	lbf
GT-100MA	102 (4.02)	2.5 (0.10)	17.5 (0.69)	22 (0.87)	80	8.2	18
GT-150IA	150 (5.91)	3.6 (0.14)	22.5 (0.89)	35 (1.38)	178	18.2	40
GT-180IA	180 (7.09)	3.6 (0.14)	24.0 (0.94)	44 (1.73)	178	18.2	40
GT-300IA	300 (11.81)	3.6 (0.14)	84.5 (3.33)	88 (3.46)	178	18.2	40
GT-200HDA	203 (7.99)	7.6 (0.30)	29.3 (1.15)	50 (1.97)	534	54.5	120