


VINYL-INSULATED MALE DISCONNECTS

- Male tab couples with female disconnects
- Male tab can be inserted and removed from the female disconnect without the use of tools for lower installation cost
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Material: Brass, PVC



Part No.	Color	Wire Range		Dimension mm (inch)				
		sq. mm.	AWG	Tab size	D	B	L	t
VT1.25-2.8S	Red	0.5-1.5	22-16	2.8x0.5 (0.11x0.02)	3.6 (0.14)	2.9 (0.11)	21.5 (0.85)	0.3 (0.01)
VT1.25-2.8	Red	0.5-1.5	22-16	2.8x0.8 (0.11x0.03)	3.6 (0.14)	2.9 (0.11)	21.5 (0.85)	0.4 (0.02)
VT1.25-4.8S	Red	0.5-1.5	22-16	4.8x0.5 (0.19x0.02)	3.6 (0.14)	4.8 (0.19)	21.5 (0.85)	0.3 (0.01)
VT1.25-4.8	Red	0.5-1.5	22-16	4.8x0.8 (0.19x0.03)	3.6 (0.14)	4.8 (0.19)	21.5 (0.85)	0.4 (0.02)
VT1.25-6.4	Red	0.5-1.5	22-16	6.4x0.8 (0.25x0.03)	3.6 (0.14)	6.4 (0.25)	21.5 (0.85)	0.4 (0.02)
VT2-2.8S	Blue	1.5-2.5	16-14	2.8x0.5 (0.11x0.02)	4.4 (0.17)	2.9 (0.11)	22.0 (0.87)	0.3 (0.01)
VT2-2.8	Blue	1.5-2.5	16-14	2.8x0.8 (0.11x0.03)	4.4 (0.17)	2.9 (0.11)	22.0 (0.87)	0.4 (0.02)
VT2-4.8S	Blue	1.5-2.5	16-14	4.8x0.5 (0.19x0.02)	4.4 (0.17)	4.8 (0.19)	22.0 (0.87)	0.3 (0.01)
VT2-4.8	Blue	1.5-2.5	16-14	4.8x0.8 (0.19x0.03)	4.4 (0.17)	4.8 (0.19)	22.0 (0.87)	0.4 (0.02)
VT2-6.4	Blue	1.5-2.5	16-14	6.4x0.8 (0.25x0.03)	4.4 (0.17)	6.4 (0.25)	22.0 (0.87)	0.4 (0.02)
VT5.5-2.8S	Yellow	4.0-6.0	12-10	2.8x0.5 (0.11x0.02)	5.4 (0.21)	2.9 (0.11)	23.5 (0.93)	0.3 (0.01)
VT5.5-2.8	Yellow	4.0-6.0	12-10	2.8x0.8 (0.11x0.03)	5.4 (0.21)	2.9 (0.11)	23.5 (0.93)	0.4 (0.02)
VT5.5-4.8S	Yellow	4.0-6.0	12-10	4.8x0.5 (0.19x0.02)	5.4 (0.21)	4.8 (0.19)	23.5 (0.93)	0.3 (0.01)
VT5.5-4.8	Yellow	4.0-6.0	12-10	4.8x0.8 (0.19x0.03)	5.4 (0.21)	4.8 (0.19)	23.5 (0.93)	0.4 (0.02)
VT5.5-6.4	Yellow	4.0-6.0	12-10	6.4x0.8 (0.25x0.03)	5.4 (0.21)	6.4 (0.25)	23.5 (0.93)	0.4 (0.02)