


EXTRA HEAVY DUTY TIES

- Extra heavy duty ties for application where higher tensile strength is required
- One-piece construction for consistent performance and reliability
- Lowest threading force of any one-piece cable tie in the industry
- Material: Polyamide 6,6, UL94V-2
- Color: All colors are available



Part No.	Length (L) mm (inch)	Width (W) mm (inch)	Max.Bundle ø mm (inch)	Min. Loop Tensile Strength		
				N	kgf	lbf
GT-230EHD	230 (9.06)	12.6 (0.50)	50 (1.97)	1112	113.4	250
GT-290EHD	295 (11.61)	12.6 (0.50)	76 (2.99)	1112	113.4	250
GT-380EHD	380 (14.96)	12.6 (0.50)	106 (4.17)	1112	113.4	250
GT-480EHD	480 (18.90)	12.6 (0.50)	120 (4.72)	1112	113.4	250
GT-580EHD	580 (22.83)	12.6 (0.50)	152 (5.98)	1112	113.4	250
GT-730EHD	730 (28.74)	12.6 (0.50)	204 (8.03)	1112	113.4	250
GT-880EHD	880 (34.65)	12.6 (0.50)	248 (9.76)	1112	113.4	250
GT-1030EHD	1020 (40.16)	12.6 (0.50)	295 (11.61)	1112	113.4	250
Releasable						
GTR-230EHD	230 (9.06)	12.6 (0.50)	50 (1.97)	1112	113.4	250
GTR-290EHD	295 (11.61)	12.6 (0.50)	76 (2.99)	1112	113.4	250
GTR-380EHD	380 (14.96)	12.6 (0.50)	106 (4.17)	1112	113.4	250
GTR-480EHD	480 (18.90)	12.6 (0.50)	120 (4.72)	1112	113.4	250
GTR-580EHD	580 (22.83)	12.6 (0.50)	152 (5.98)	1112	113.4	250
GTR-730EHD	730 (28.74)	12.6 (0.50)	204 (8.03)	1112	113.4	250
GTR-880EHD	880 (34.65)	12.6 (0.50)	248 (9.76)	1112	113.4	250
GTR-1030EHD	1020 (40.16)	12.6 (0.50)	295 (11.61)	1112	113.4	250