



DOUBLE LOOP TIES

- The tie's second loop may also serve as a positioning device for a single bundle
- Double head ties can be used for installation of a second parallel cable run without the need for additional cable ties
- Material: Polyamide 6,6, UL94V-2
- Color: All colors are available



Part No.	Length (L) mm (inch)	Width (W) mm (inch)	Max.Bundle ϕ mm (inch)	Min. Loop Tensile Strength		
				N	kgf	lbf
GTB-200ST	195 (7.68)	4.8 (0.19)	a: ϕ 47 (1.85) b: ϕ 45 (1.77)	222	22.6	50
GTB-300ST	303 (11.93)	4.8 (0.19)	a: ϕ 72 (2.83) b: ϕ 70 (2.76)	222	22.6	50
GTB-370ST	372 (14.65)	4.8 (0.19)	a: ϕ 100 (3.94) b: ϕ 97 (3.82)	222	22.6	50

MOUNTABLE HEAD TIES

- These screw mount cable ties have a built in mounting holes
- Once fastened around the cables the bundle can be simply secured to the panel with a screw or bolt
- Material : Polyamide 6,6, UL94V-2
- Color: All colors are available



Part No.	Length (L) mm (inch)	Width (W) mm (inch)	Max.Bundle ϕ mm (inch)	Min. Loop Tensile Strength			Mounting Hole ϕ mm (inch)
				N	kgf	lbf	
GTM-110M	110 (4.33)	2.5 (0.10)	22 (0.87)	80	8.2	18	3.2 (0.13)
GTM-150I	150 (5.91)	3.6 (0.14)	32 (1.26)	178	18.2	40	4.2 (0.17)
GTM-200ST	200 (7.87)	4.8 (0.19)	47 (1.85)	222	22.6	50	5.2 (0.20)
GTM-216ST	216 (8.50)	4.8 (0.19)	53 (2.09)	222	22.6	50	5.2 (0.20)
GTM-300ST	309 (12.17)	4.8 (0.19)	76 (2.99)	222	22.6	50	5.2 (0.20)
GTM-370ST	380 (14.96)	4.8 (0.19)	102 (4.02)	222	22.6	50	5.2 (0.20)
GTM-200HD	215 (8.46)	7.6 (0.30)	47 (1.85)	534	54.5	120	5.7 (0.22)
GTM-300HD	313 (12.32)	7.6 (0.30)	76 (2.99)	534	54.5	120	5.7 (0.22)
GTM-380HD	382 (15.04)	7.6 (0.30)	98 (3.86)	534	54.5	120	5.7 (0.22)