



HUA WEI INDUSTRIAL CO., LTD.

No.1, Gongyequ 26th Rd., Nantun Dist., Taichung City 408, Taiwan, R.O.C. TEL: +886-4-23597777 FAX: +886-4-23596705~6 http://www.hwlok.com





CABLE TIE INSTALLATION TOOLS

- Extremely light and ergonomic design to reduce user stress for continuous use.
- An adjustable tension knob makes cutting more precision.
- Quickly and safely cuts nylon cable ties and avoids the risk of injury.
- · Customized colors are available.
- Main Material: Plastic / Metal
- Net Weight: 230 g (0.5 lbs)





Part No.	Applicable Cable Ties		Dimensions	Spare Blade
	Width mm (inch)	Thickness mm (inch)	mm (inch)	Replacement Kit
GIT-703	2.5~4.8 (0.10~0.19)	1.0~1.6 (0.04~0.06)	190x140x36 (7.48x5.51x1.41)	No
GIT-703 Plus				Yes

OPERATING INSTRUCTIONS











- 1. Wrap the cable tie on the object and tighten it up.
- 2. Adjust tension settings by rotating the tension control knob.
- 3. Insert the cable tie strap through the tension tool and place the cutting head against the head of the cable tie.
- 4. Press the trigger until the cable tie strap is cut off.
- 5. Finish.

TENSION ADJUSTMENT

Tool Setting	1-3	3-5	5-8
Cable Tie Type	Miniature	Intermediate	Standard
Cable Tie Width	2.5mm (0.10 inch)	3.6mm (0.14inch)	4.8mm (0.19inch)

BLADE REPLACEMENT (GIT-703 Plus)













- 1. Firstly, adjust the tension to zero. Release the cap of the tension knob with a coin. Take out the screwdriver.
- 2. Unscrew the blade guard screw with the attached screwdriver.
- 3. Pull out the blade guard. Remove the used blade.
- 4. Remove the sticker on the screwdriver and take out the new blade carefully.
- 5. Put the new blade on the tension tool. Make sure the chamfered corner is in the upper right position. Put the blade guard back.
- 6. Reinstall the screw. Do not over tighten it. Put the attached screwdriver back to the tension tool. Finish.

More Video and Instruction



Technical Manual GIT-703 / GIT-703 Plus

HUA WEI INDUSTRIAL CO., LTD.