

DIN 3017



German Type Hose Clamp

The German type hose clamp with non-perforated design helps to avoid scratching the hose surface during Installation. Thence, the effect of protecting to avoid gas or liquid leaking from the tube.

- Smooth embossed non-perforated band and flared edge prevent hoses from shearing and fray during installation



- Elegant outside appearance

- Material & clamping range stamp on the band




German Type Hose Clamp

- The band has Germany type wolf teeth designed for reduce clamping chafing and damage
- Precision-engineered and elegant appearance.
- In accordance with the DIN 3017 and RoHS & REACH standard.
- Material and clamping range are stamped on the band.
- W4 stainless steel is superior corrosion resistance.



Part No.	Band Width		Clamping Range Ø				Hex. Head Screw
	mm	inch	Min. mm	Max. mm	Min. inch	Max. inch	
GHC-1/2S	9	0.35	8	12	5/16	1/2	7mm
GHC-5/8S			10	16	3/8	5/8	
GHC-3/4S			12	20	1/2	3/4	
GHC-7/8S			12	22	1/2	7/8	
GHC-1S			16	25	5/8	1	
GHC-1-1/16S			16	27	5/8	1-1/16	
GHC-1-1/4S			20	32	3/4	1-1/4	
GHC-1-5/8S			25	40	1	1-5/8	
GHC-1-3/4S			30	45	1-3/16	1-3/4	
GHC-2S			32	50	1-1/4	2	
GHC-2-3/8S			40	60	1-5/8	2-3/8	
GHC-1	12	0.47	16	25	5/8	1	
GHC-1-1/16			16	27	5/8	1-1/16	
GHC-1-1/4			20	32	3/4	1-1/4	
GHC-1-5/8			25	40	1	1-5/8	
GHC-1-3/4			30	45	1-3/16	1-3/4	
GHC-2			32	50	1-1/4	2	
GHC-2-3/8			40	60	1-5/8	2-3/8	
GHC-2-3/4			50	70	2	2-3/4	
GHC-3-1/8			60	80	2-3/8	3-1/8	
GHC-3-1/2			70	90	2-3/4	3-1/2	
GHC-4			80	100	3-1/8	4	
GHC-4-3/8			90	110	3-1/2	4-3/8	
GHC-4-3/4			100	120	4	4-3/4	
GHC-5-1/8			110	130	4-3/8	5-1/8	
GHC-5-1/2			120	140	4-3/4	5-1/2	
GHC-5-7/8			130	150	5-1/8	5-7/8	
GHC-6-1/4			140	160	5-1/2	6-1/4	
GHC-6-3/4			150	170	5-7/8	6-3/4	
GHC-7			160	180	6-1/4	7	



Tightening Torque

Band Width	Rec. Installation Torque
9mm	3.0 Nm (26 lbf-in)
12mm	4.0 Nm (35 lbf-in)

Material

Material Type	Band	Housing	Screw
W2 (430 S.S.)	AISI 430 S.S.	AISI 430 S.S.	Plated Carbon Steel 
W4 (304 S.S.)	AISI 304 S.S.	AISI 304 S.S.	AISI 304 S.S. 

HUA WEI INDUSTRIAL CO., LTD.

No.1, Gongyequ 26th Rd., Nantun Dist., Taichung City 408, Taiwan, R.O.C.

TEL: +886-4-23597777

FAX: +886-4-23596705-6

Email: service@hwlok.com <http://www.hwlok.com>

