



www.hwlok.com



Heat Stabilized Cable Ties



+120°C

+248°F



80 ~ 534 N
8.2~54.5 Kgf/ 18~120 lbf



-40 ~ 120 °C
-40 ~ 248 °F



HUA WEI INDUSTRIAL CO., LTD.

No.1, Gongyequ 26th Rd., Nantun Dist., Taichung City 408, Taiwan, R.O.C.

TEL: +886-4-23597777

FAX: +886-4-23596705~6

Email:service@hwlok.com http://www.hwlok.com





www.hwlok.com

HEAT STABILIZED CABLE TIES

- Heat stabilized cable ties (PA66HS) for temperatures up to +120 °C
- Internal serrations allowing for a positive hold onto cable and pipe bundles
- The design of the head guarantees a high tensile strength while allowing a very low insertion force
- Available in a wide range of sizes to cover almost every application
- Material :PA6,6 heat stabilized
- Flammability Rating: UL94V-2
- Color: Black, Red



Part No.	Length (L) mm (inch)	Width (W) mm (inch)	Max.Bundle ø mm (inch)	Min. Loop Tensile Strength			Recommended Tensioning Tools
				N	kgf	lbf	
GT-80MH	80 (3.15)	2.4 (0.09)	15 (0.59)	80	8.2	18	 GIT-703
GT-100MH	100 (3.94)	2.5 (0.10)	22 (0.87)	80	8.2	18	
GT-120MH	120 (4.72)	2.5 (0.10)	30 (1.18)	80	8.2	18	
GT-140MH	140 (5.51)	2.5 (0.10)	33 (1.30)	80	8.2	18	
GT-160MH	160 (6.30)	2.5 (0.10)	40 (1.57)	80	8.2	18	
GT-200MH	200 (7.87)	2.5 (0.10)	53 (2.09)	80	8.2	18	
GT-140IH	140 (5.51)	3.6 (0.14)	33 (1.30)	178	18.2	40	
GT-200IH	200 (7.87)	3.6 (0.14)	53 (2.09)	178	18.2	40	
GT-250IH	250 (9.84)	3.6 (0.14)	65 (2.56)	178	18.2	40	
GT-300IH	300 (11.81)	3.6 (0.14)	76 (2.99)	178	18.2	40	
GT-370IH	370 (14.57)	3.6 (0.14)	102 (4.02)	178	18.2	40	
GT-160STH	160 (6.30)	4.8 (0.19)	38 (1.50)	222	22.6	50	
GT-190STH	190 (7.48)	4.8 (0.19)	46 (1.81)	222	22.6	50	
GT-200STH	200 (7.87)	4.8 (0.19)	50 (1.97)	222	22.6	50	
GT-250STH	250 (9.84)	4.8 (0.19)	60 (2.36)	222	22.6	50	
GT-300STH	300 (11.81)	4.8 (0.19)	76 (2.99)	222	22.6	50	
GT-370STH	370 (14.57)	4.8 (0.19)	102 (4.02)	222	22.6	50	
GT-430STH	430 (16.93)	4.8 (0.19)	110 (4.33)	222	22.6	50	
GT-530STH	530 (20.87)	4.8 (0.19)	140 (5.51)	222	22.6	50	
GT-200HDH	200 (7.87)	7.6 (0.30)	50 (1.97)	534	54.5	120	 GIT-704G
GT-300HDH	300 (11.81)	7.6 (0.30)	76 (2.99)	534	54.5	120	
GT-370HDH	370 (14.57)	7.6 (0.30)	102 (4.02)	534	54.5	120	
GT-430HD-SH	430 (16.93)	7.6 (0.30)	125 (4.92)	534	54.5	120	
GT-540HD-SH	533 (20.98)	7.6 (0.30)	140 (5.51)	534	54.5	120	
GT-750HD-SH	750 (29.53)	7.6 (0.30)	218 (8.58)	534	54.5	120	

* Other sizes available.
* Subject to minimum order request.

