




POLYPROPYLENE CABLE TIES



Polypropylene Cable Ties are higher chemical resistance when exposed to various solutions of salts, acids and bases. Ideal for use in the chemical process industry and related harsh environments.




-40 ~ 115 °C
-40 ~ 239 °F



Polypropylene Cable Ties

- Polypropylene is superior resistance to chemical attack.
- Low density of PP cable ties can float the surface of most liquids, so it is easily to seen and removed.
- Continuous operating temperatures up to 115 ° C (239° F).
- One-piece construction for consistent performance and reliability.
- Internal serrations allowing for a positive hold.
- Material Flammability Rating: UL94HB.
- Color: Black, green



| Part No. | Length (L) mm (inch) | Width (W) mm (inch) | Max.Bundle ϕ mm (inch) | Min. Loop Tensile Strength | | |
|--------------|-------------------------|------------------------|--------------------------------|----------------------------|------|-----|
| | | | | N | kgf | lbf |
| GT-100M-PP | 100 (3.94) | 2.5 (0.10) | 22 (0.87) | 49 | 5.0 | 11 |
| GT-140I-PP | 140 (5.51) | 3.6 (0.14) | 33 (1.30) | 89 | 9.1 | 20 |
| GT-150I-PP | 150(5.91) | 3.6 (0.14) | 35(1.38) | 89 | 9.1 | 20 |
| GT-190ST-PP | 190 (7.48) | 4.8 (0.19) | 46 (1.81) | 137 | 14.0 | 30 |
| GT-200ST-PP | 200 (7.87) | 4.8 (0.19) | 50 (1.97) | 137 | 14.0 | 30 |
| GT-300ST-PP | 300 (11.81) | 4.8 (0.19) | 76 (2.99) | 137 | 14.0 | 30 |
| GT-370ST-PP | 370 (14.57) | 4.8 (0.19) | 102 (4.02) | 137 | 14.0 | 30 |
| GT-200HD-PP | 200 (7.87) | 7.6 (0.30) | 50 (1.97) | 267 | 27.2 | 60 |
| GT-240HD-PP | 242 (9.53) | 7.6 (0.30) | 63 (2.48) | 267 | 27.2 | 60 |
| GT-300HD-PP | 300 (11.81) | 7.6 (0.30) | 76 (2.99) | 267 | 27.2 | 60 |
| GT-370HD-PP | 370 (14.57) | 7.6 (0.30) | 102 (4.02) | 267 | 27.2 | 60 |
| GT390HD-S-PP | 390(15.35) | 7.6 (0.30) | 108(4.25) | 267 | 27.2 | 60 |



HUA WEI INDUSTRIAL CO., LTD.

No.1, Gongyequ 26th Rd., Nantun Dist., Taichung City 408, Taiwan
 ☎ +886-4-23597777 ✉ service@hwlok.com 🌐 www.hwlok.com

