

Fast Installation

Precise Locking

VTough Hold

Longer Life

STEEL BARB CABLE TIES





- Anti-Vibration
- Environmental Resistance
- UV Resistance
- Corrosion Resistance











STEEL BARB CABLE TIES

FEATURES:

- Easy Threading, Installation and Fastening
- Precise Locking and Infinite Positioning
- Safety, Reliability and Tough Hold
- Durable Stainless Steel Lock and Anti-Slip
- Labor Saving and High Performance
- UV Resistant (Specify Color)
- Operating Temperature: -40 ~ 85°C (-40 ~ 185°F)
- Min. Installation Temperature: -20°C (-4°F)
- Material: PA66, Stainless Steel Locking Barb
- Material Flame Rating: UL94V-2

APPLICATIONS:

- Suitable for High-Speed Vibration Environment
- Used in Harsh Environments
- Used in Temperature Fluctuations Environment



- Suitable for Precision Installation
- Applications Requiring Durability and Performance

Aerospace	High-speed Rail		echanical quipment anufacturing	ts	Smart Home	System	
Part No.	Color	Length (L) mm (inch)	Width (W) mm (inch)	Max.Bundle ø mm (inch)	Min. Loop Tensile Strength		
					N	kgf	lbf
GTSB-200ST	Natural	200 (7.87)	4.7 (0.19)	50 (1.97)	22.6	50	222
GTSB-280ST	Natural	280 (11.02)	4.7 (0.19)	70 (2.76)	22.6	50	222
GTSB-300ST	Natural	300 (11.81)	4.7 (0.19)	76 (2.99)	22.6	50	222
GTSB-370ST	Natural	370 (14.57)	4.7 (0.19)	102 (4.02)	22.6	50	222
GTSB-200STUV	Black	200 (7.87)	4.7 (0.19)	50 (1.97)	22.6	50	222
GTSB-280STUV	Black	280 (11.02)	4.7 (0.19)	70 (2.76)	22.6	50	222
GTSB-300STUV	Black	300 (11.81)	4.7 (0.19)	76 (2.99)	22.6	50	222
GTSB-370STUV	Black	370 (14.57)	4.7 (0.19)	102 (4.02)	22.6	50	222

*All colors available. For customized material requests, please contact us.

Head

- Ergonomic design reduces hand fatigue.
- Reduces friction, extending the lifespan of bundled items.

Hole

- Easy threading, reduces installation effort.
- · Silently threading.

Tongue

- Stainless steel mechanism, precise locking.
- Infinite adjustment.
- · Locking and anti-slip.
- Built for tough conditions. Improves tensile strength performance.

HUA WEI INDUSTRIAL CO., LTD.

No.1, Gongyequ 26th Rd., Nantun Dist., Taichung City 408, Taiwan TEL: +886-4-23597777 FAX: +886-4-23596705~6 Email:service@hwlok.com http://www.hwlok.com



Tail

- Easy grip in tight spaces, low light, or with gloves.
- Reliable tightening, even in wet and cold conditions.

 Body
Eliminates stress. Vibration-resistant.

CE REACH ROHS



www.hwlok.com