

# STRIPED CABLE TIES

- One-piece construction with lowest threading force
- 25 color combinations ideal for telephone and data cable binder marking
- High-contrast color stripes for instant, permanent identification of binder
- Operating Temperature:  
-40°C to 85°C (-40°F to 185°F)
- Material: Polyamide 6.6, UL94V-2



Part No.	Tie Color	Stripe Color	Length (L)		Width (W)		Max. Bundle Ø		Loop Tensile Strength			Std. Pkg. Qty.
			mm	in	mm	in	mm	in	N	kgf	lbf	
ST-100MBL-WT	Blue	White	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MBL-RD		Red	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MBL-BK		Black	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MBL-YL		Yellow	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MBL-PL		Violet	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MOR-WT	Orange	White	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MOR-RD		Red	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MOR-BK		Black	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MOR-YL		Yellow	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MOR-PL		Violet	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MGN-WT	Green	White	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MGN-RD		Red	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MGN-BK		Black	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MGN-YL		Yellow	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MGN-PL		Violet	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MBN-WT	Brown	White	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MBN-RD		Red	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MBN-BK		Black	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MBN-YL		Yellow	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MBN-PL		Violet	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MSL-WT	Slate	White	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MSL-RD		Red	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MSL-BK		Black	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MSL-YL		Yellow	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50
ST-100MSL-PL		Violet	100.0	3.94	2.5	0.10	22.0	0.87	80	8.2	18	50

