



Waterproof




Anti-corrosion



Easy to Use

Waterproof Wire Connectors

- Tough thermoplastic, UL 94V-2 flame-retardant shell for 105°C (221°F).
- Rated to 600V max.
- Screw-on wire connectors pre-filled with dielectric silicone sealant. Comply with UL standard.
- Waterproof, dustproof and corrosion proof.
- For use in dry, damp, wet, bury locations. Not for use in continual submersion applications. One time use only. Do not Reuse Connector.
- Easy to use wire connectors nuts.
- Material: Shell - Polypropylene (PP). Spring - calvanized carbon steel. Fillers - dielectric silicone sealant.



Landscape Lighting



Irrigation System



Harbor Electrical Outlets


IP68  

| Part No. | Temp Rating | Dimension mm(inch) | | | Voltage | Suitable Wire AWG | Color |
|----------|-----------------|--------------------|-------------|-------------|---------|-------------------|------------|
| | | A | B | C | | | |
| R3-R | 105°C (221 °F) | 40.9 (1.61) | 16.5 (0.65) | 25.2 (0.99) | 600V | 20 - 10 | Blue/Red |
| R6-R | 105°C (221 °F) | 47.2 (1.86) | 16.5 (0.65) | 26.5 (1.04) | 600V | 20 - 8 | Blue/Black |


Easy to Use




Strip the wire with the lead for 13 ~ 16mm (0.51 ~ 0.63 inch).



Insert the spliced wire until the wire touches the bottom of the wire connector.



Turn clockwise until the wire is very tight with at least 2 twists visible



Fixed end cap secures sealant and protects connection

HUA WEI INDUSTRIAL CO., LTD.

No.1, Gongyequ 26th Rd., Nantun Dist., Taichung City 408, Taiwan
 TEL: +886-4-23597777 FAX: +886-4-23596705~6
 Email: service@hwlok.com http://www.hwlok.com



www.hwlok.com