


# VINYL-INSULATED RING TERMINALS

- Insulation support helps to prevent wire damage in bending applications
- Copper tube with tin plated end sleeves with insulation PVC



Part No.	Color	Wire Range		Dimension mm (inch)				Stud Size	
		sq. mm.	AWG	B	d2	L	t	mm	inch
VR1.25-3	Red	0.5-1.5	22-16	5.5 (0.22)	3.2 (0.13)	17.5 (0.69)	0.8 (0.03)	M3	#5
VR1.25-3.5	Red	0.5-1.5	22-16	5.5 (0.22)	3.7 (0.15)	17.5 (0.69)	0.8 (0.03)	M3.5	#6
VR1.25-3.5L	Red	0.5-1.5	22-16	6.6 (0.26)	3.7 (0.15)	20.4 (0.80)	0.8 (0.03)	M3.5	#6
VR1.25-4	Red	0.5-1.5	22-16	8.0 (0.31)	4.3 (0.17)	21.7 (0.85)	0.8 (0.03)	M4	#8
VR1.25-4M	Red	0.5-1.5	22-16	6.6 (0.26)	4.3 (0.17)	20.4 (0.80)	0.8 (0.03)	M4	#8
VR1.25-5	Red	0.5-1.5	22-16	8.0 (0.31)	5.3 (0.21)	21.7 (0.85)	0.8 (0.03)	M5	#10
VR1.25-6	Red	0.5-1.5	22-16	11.6 (0.46)	6.4 (0.25)	27.6 (1.09)	0.8 (0.03)	M6	1/4"
VR1.25-8	Red	0.5-1.5	22-16	11.6 (0.46)	8.4 (0.33)	27.6 (1.09)	0.8 (0.03)	M8	5/16"
VR1.25-10	Red	0.5-1.5	22-16	13.7 (0.54)	10.5 (0.41)	31.5 (1.24)	0.8 (0.03)	M10	3/8"
VR1.25-12	Red	0.5-1.5	22-16	19.0 (0.75)	13.0 (0.51)	35.0 (1.38)	0.8 (0.03)	M12	1/2"
VR2-3M	Blue	1.5-2.5	16-14	6.6 (0.26)	3.2 (0.13)	20.6 (0.81)	0.8 (0.03)	M3	#5
VR2-3	Blue	1.5-2.5	16-14	8.5 (0.33)	3.2 (0.13)	23.0 (0.91)	0.8 (0.03)	M3	#5
VR2-3.5	Blue	1.5-2.5	16-14	6.6 (0.26)	3.7 (0.15)	20.6 (0.81)	0.8 (0.03)	M3.5	#6
VR2-3.5L	Blue	1.5-2.5	16-14	8.5 (0.33)	3.7 (0.15)	23.0 (0.91)	0.8 (0.03)	M3.5	#6
VR2-4	Blue	1.5-2.5	16-14	8.5 (0.33)	4.3 (0.17)	23.0 (0.91)	0.8 (0.03)	M4	#8
VR2-4M	Blue	1.5-2.5	16-14	6.6 (0.26)	4.3 (0.17)	20.8 (0.82)	0.8 (0.03)	M4	#8
VR2-5M	Blue	1.5-2.5	16-14	8.5 (0.33)	5.3 (0.21)	23.0 (0.91)	0.8 (0.03)	M5	#10
VR2-5	Blue	1.5-2.5	16-14	9.5 (0.37)	5.3 (0.21)	23.0 (0.91)	0.8 (0.03)	M5	#10
VR2-6	Blue	1.5-2.5	16-14	12.0 (0.47)	6.4 (0.25)	28.1 (1.11)	0.8 (0.03)	M6	1/4"
VR2-8	Blue	1.5-2.5	16-14	12.0 (0.47)	8.4 (0.33)	28.1 (1.11)	0.8 (0.03)	M8	5/16"
VR2-10	Blue	1.5-2.5	16-14	13.7 (0.54)	10.5 (0.41)	31.9 (1.26)	0.8 (0.03)	M10	3/8"
VR2-12	Blue	1.5-2.5	16-14	19.0 (0.75)	13.0 (0.51)	35.5 (1.40)	0.8 (0.03)	M12	1/2"
VR5.5-3	Yellow	4.0-6.0	12-10	9.5 (0.37)	3.2 (0.13)	26.7 (1.05)	1.0 (0.04)	M3	#5
VR5.5-3.5	Yellow	4.0-6.0	12-10	9.5 (0.37)	3.7 (0.15)	26.7 (1.05)	1.0 (0.04)	M3.5	#6
VR5.5-4S	Yellow	4.0-6.0	12-10	7.4 (0.29)	4.3 (0.17)	26.7 (1.05)	1.0 (0.04)	M4	#8
VR5.5-4	Yellow	4.0-6.0	12-10	9.5 (0.37)	4.3 (0.17)	26.7 (1.05)	1.0 (0.04)	M4	#8
VR5.5-5	Yellow	4.0-6.0	12-10	9.5 (0.37)	5.3 (0.21)	26.7 (1.05)	1.0 (0.04)	M5	#10
VR5.5-5S	Yellow	4.0-6.0	12-10	7.4 (0.29)	5.3 (0.21)	26.7 (1.05)	1.0 (0.04)	M5	#10
VR5.5-6	Yellow	4.0-6.0	12-10	12.0 (0.47)	6.4 (0.25)	32.7 (1.29)	1.0 (0.04)	M6	1/4"
VR5.5-8	Yellow	4.0-6.0	12-10	15.0 (0.59)	8.4 (0.33)	34.9 (1.37)	1.0 (0.04)	M8	5/16"
VR5.5-10	Yellow	4.0-6.0	12-10	15.0 (0.59)	10.5 (0.41)	34.9 (1.37)	1.0 (0.04)	M10	3/8"
VR5.5-12	Yellow	4.0-6.0	12-10	19.2 (0.76)	13.0 (0.51)	39.9 (1.57)	1.0 (0.04)	M12	1/2"