


NON-INSULATED BLADE TERMINALS

- Flat blade design to prevent damage to the wire from over tightening, resulting in a reliable electrical connection
- For use with blade-type terminal blocks
- Brazed seam protects terminal barrel from splitting during the crimping process
- Material: Copper



Part No.	Wire Range		Dimension mm (inch)				
	sq. mm.	AWG	d1	B	F	L	t
B1.25-9SB	0.5-1.5	22-16	1.9 (0.07)	2.3 (0.09)	9.0 (0.35)	14.0 (0.55)	0.8 (0.03)
B1.25-9B	0.5-1.5	22-16	1.9 (0.07)	2.7 (0.11)	9.0 (0.35)	14.0 (0.55)	0.8 (0.03)
B1.25-12B	0.5-1.5	22-16	1.9 (0.07)	3.0 (0.12)	12.0 (0.47)	16.0 (0.63)	0.8 (0.03)
B1.25-14.5B	0.5-1.5	22-16	1.9 (0.07)	3.0 (0.12)	14.5 (0.57)	19.5 (0.77)	0.8 (0.03)
B1.25-18B	0.5-1.5	22-16	1.9 (0.07)	2.5 (0.10)	18.0 (0.71)	23.0 (0.91)	0.8 (0.03)
B2-9B	1.5-2.5	16-14	2.5 (0.10)	2.8 (0.11)	9.0 (0.35)	14.0 (0.55)	0.8 (0.03)
B2-16B	1.5-2.5	16-14	2.5 (0.10)	2.9 (0.11)	16.0 (0.63)	21.0 (0.83)	0.8 (0.03)
B2-18B	1.5-2.5	16-14	2.5 (0.10)	2.5 (0.10)	18.0 (0.71)	23.0 (0.91)	0.8 (0.03)
B5.5-10B	4.0-6.0	12-10	3.6 (0.14)	2.8 (0.11)	10.0 (0.39)	16.5 (0.65)	1.0 (0.04)
B5.5-13B	4.0-6.0	12-10	3.6 (0.14)	4.6 (0.18)	13.0 (0.51)	19.5 (0.77)	1.0 (0.04)
B5.5-18B	4.0-6.0	12-10	3.6 (0.14)	4.5 (0.18)	18.0 (0.71)	24.5 (0.96)	1.0 (0.04)