


VINYL-INSULATED BLADE TERMINALS

- Flat blade design to prevent damage to the wire from over tightening, resulting in a reliable electrical connection
- For use with blade-type terminal blocks
- Insulation support helps to prevent wire damage in bending applications
- Material: Copper tube with tin plated end sleeves with insulation PVC



Part No.	Color	Wire Range		Dimension mm (inch)				
		sq. mm.	AWG	D	B	F	L	t
VB1.25-9S	Red	0.5-1.5	22-16	4.3 (0.17)	2.3 (0.09)	9.0 (0.35)	19.5 (0.77)	0.8 (0.03)
VB1.25-9	Red	0.5-1.5	22-16	4.3 (0.17)	2.7 (0.11)	9.0 (0.35)	19.5 (0.77)	0.8 (0.03)
VB1.25-12	Red	0.5-1.5	22-16	4.3 (0.17)	3.0 (0.12)	12.0 (0.47)	25.0 (0.98)	0.8 (0.03)
VB1.25-14.5	Red	0.5-1.5	22-16	4.3 (0.17)	3.0 (0.12)	14.5 (0.57)	21.5 (0.85)	0.8 (0.03)
VB1.25-18	Red	0.5-1.5	22-16	4.3 (0.17)	2.5 (0.10)	18.0 (0.71)	28.5 (1.12)	0.8 (0.03)
VB2-9	Blue	1.5-2.5	16-14	4.7 (0.19)	2.8 (0.11)	9.0 (0.35)	20.0 (0.79)	0.8 (0.03)
VB2-16	Blue	1.5-2.5	16-14	4.7 (0.19)	2.9 (0.11)	16.0 (0.63)	27.0 (1.06)	0.8 (0.03)
VB2-18	Blue	1.5-2.5	16-14	4.7 (0.19)	2.5 (0.10)	18.0 (0.71)	29.0 (1.14)	0.8 (0.03)
VB5.5-10	Yellow	4.0-6.0	12-10	6.7 (0.26)	2.8 (0.11)	10.0 (0.39)	24.0 (0.94)	1.0 (0.04)
VB5.5-13	Yellow	4.0-6.0	12-10	6.7 (0.26)	4.5 (0.18)	13.0 (0.51)	27.0 (1.06)	1.0 (0.04)
VB5.5-18	Yellow	4.0-6.0	12-10	6.7 (0.26)	4.5 (0.18)	18.0 (0.71)	32.0 (1.26)	1.0 (0.04)