


VINYL-INSULATED FEMALE DISCONNECTORS

- Disconnect can be inserted and removed from the male tab without the use of tools for lower installation cost
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection
- Material: Brass, PVC



Part No.	Color	Wire Range		Dimension mm (inch)				
		sq. mm.	AWG	Tab size	D	B	L	t
VU1.25-2.8S	Red	0.5-1.5	22-16	2.8x0.5 (0.11x0.02)	3.6 (0.14)	3.2 (0.13)	18.5 (0.73)	0.3 (0.01)
VU1.25-2.8	Red	0.5-1.5	22-16	2.8x0.8 (0.11x0.03)	3.6 (0.14)	3.2 (0.13)	18.5 (0.73)	0.3 (0.01)
VU1.25-4.8S	Red	0.5-1.5	22-16	4.8x0.5 (0.19x0.02)	3.6 (0.14)	5.0 (0.20)	19.0 (0.75)	0.4 (0.02)
VU1.25-4.8	Red	0.5-1.5	22-16	4.8x0.8 (0.19x0.03)	3.6 (0.14)	5.0 (0.20)	19.0 (0.75)	0.4 (0.02)
VU1.25-5.2	Red	0.5-1.5	22-16	5.2x0.5 (0.20x0.02)	3.6 (0.14)	5.6 (0.22)	20.0 (0.79)	0.4 (0.02)
VU1.25-6.4	Red	0.5-1.5	22-16	6.4x0.8 (0.25x0.03)	3.6 (0.14)	6.7 (0.26)	21.0 (0.83)	0.4 (0.02)
VU2-2.8S	Blue	1.5-2.5	16-14	2.8x0.5 (0.11x0.02)	4.4 (0.17)	3.2 (0.13)	18.5 (0.73)	0.3 (0.01)
VU2-2.8	Blue	1.5-2.5	16-14	2.8x0.8 (0.11x0.03)	4.4 (0.17)	3.2 (0.13)	18.5 (0.73)	0.3 (0.01)
VU2-4.8S	Blue	1.5-2.5	16-14	4.8x0.5 (0.19x0.02)	4.4 (0.17)	5.0 (0.20)	19.0 (0.75)	0.4 (0.02)
VU2-4.8	Blue	1.5-2.5	16-14	4.8x0.8 (0.19x0.03)	4.4 (0.17)	5.0 (0.20)	19.0 (0.75)	0.4 (0.02)
VU2-5.2	Blue	1.5-2.5	16-14	5.2x0.5 (0.20x0.02)	4.4 (0.17)	5.6 (0.22)	20.0 (0.79)	0.4 (0.02)
VU2-6.4	Blue	1.5-2.5	16-14	6.4x0.8 (0.25x0.03)	4.4 (0.17)	6.7 (0.26)	21.0 (0.83)	0.4 (0.02)
VU5.5-2.8S	Yellow	4.0-6.0	12-10	2.8x0.5 (0.11x0.02)	5.4 (0.21)	3.2 (0.13)	22.0 (0.87)	0.4 (0.02)
VU5.5-2.8	Yellow	4.0-6.0	12-10	2.8x0.8 (0.11x0.03)	5.4 (0.21)	3.2 (0.13)	22.0 (0.87)	0.4 (0.02)
VU5.5-4.8S	Yellow	4.0-6.0	12-10	4.8x0.5 (0.19x0.02)	5.4 (0.21)	5.0 (0.20)	22.0 (0.87)	0.4 (0.02)
VU5.5-4.8	Yellow	4.0-6.0	12-10	4.8x0.8 (0.19x0.03)	5.4 (0.21)	5.0 (0.20)	22.0 (0.87)	0.4 (0.02)
VU5.5-6.4	Yellow	4.0-6.0	12-10	6.4x0.8 (0.25x0.03)	5.4 (0.21)	6.7 (0.26)	25.0 (0.98)	0.4 (0.02)
VU5.5-9.4	Yellow	4.0-6.0	12-10	9.4x1.2 (0.37x0.05)	5.4 (0.21)	9.9 (0.39)	29.0 (1.14)	0.5 (0.02)