


# VINYL-FULLY INSULATED FEMALE DISCONNECTORS


- Disconnect can be inserted and removed from the male tab without the use of tools for lower installation cost
- Fully insulated design provides protection from electrical shorts
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection
- Material: Brass, PVC



Part No.	Color	Wire Range		Dimension mm (inch)				
		sq. mm.	AWG	Tab size	D	B	L	t
FVU1.25-4.8S	Red	0.5-1.5	22-16	4.8x0.5 (0.19x0.02)	4.0 (0.16)	5.0 (0.20)	20.0 (0.79)	0.4 (0.02)
FVU1.25-4.8	Red	0.5-1.5	22-16	4.8x0.8 (0.19x0.03)	4.0 (0.16)	5.0 (0.20)	20.0 (0.79)	0.4 (0.02)
FVU1.25-6.4	Red	0.5-1.5	22-16	6.4x0.8 (0.25x0.03)	4.0 (0.16)	6.7 (0.26)	22.0 (0.87)	0.4 (0.02)
FVU2-4.8S	Blue	1.5-2.5	16-14	4.8x0.5 (0.19x0.02)	4.5 (0.18)	5.0 (0.20)	20.0 (0.79)	0.4 (0.02)
FVU2-4.8	Blue	1.5-2.5	16-14	4.8x0.8 (0.19x0.03)	4.5 (0.18)	5.0 (0.20)	20.0 (0.79)	0.4 (0.02)
FVU2-6.4	Blue	1.5-2.5	16-14	6.4x0.8 (0.25x0.03)	4.5 (0.18)	6.7 (0.26)	22.5 (0.89)	0.4 (0.02)
FVU5.5-4.8S	Yellow	4.0-6.0	12-10	4.8x0.5 (0.19x0.02)	5.5 (0.22)	5.0 (0.20)	23.5 (0.93)	0.4 (0.02)
FVU5.5-4.8	Yellow	4.0-6.0	12-10	4.8x0.8 (0.19x0.03)	5.5 (0.22)	5.0 (0.20)	23.5 (0.93)	0.4 (0.02)
FVU5.5-6.4	Yellow	4.0-6.0	12-10	6.4x0.8 (0.25x0.03)	5.5 (0.22)	6.7 (0.26)	24.0 (0.94)	0.4 (0.02)

# VINYL-INSULATED PIGGYBACK DISCONNECTORS

- Combination of female disconnect and male tab allows versatility in points of connection
- Multiple connection points allow additional circuits to be added to existing equipment without expensive rework
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Material: Brass, PVC



Part No.	Color	Wire Range		Dimension mm (inch)					
		sq. mm.	AWG	Tab size	D	B	L	b	t
VPB1.25-6.4	Red	0.5-1.5	22-16	6.4x0.8 (0.25x0.03)	3.6 (0.14)	6.7 (0.26)	22.0 (0.87)	6.4 (0.25)	0.4 (0.02)
VPB2-6.4	Blue	1.5-2.5	16-14	6.4x0.8 (0.25x0.03)	4.4 (0.17)	6.7 (0.26)	22.0 (0.87)	6.4 (0.25)	0.4 (0.02)
VPB5.5-6.4	Yellow	4.0-6.0	12-10	6.4x0.8 (0.25x0.03)	5.4 (0.21)	6.7 (0.26)	23.0 (0.91)	6.4 (0.25)	0.4 (0.02)