


## VINYL-INSULATED MALE BULLET CONNECTORS


- Male bullet connector couples with female one
- Male bullet connector can be inserted and removed from the female disconnect without the use of tools for lower installation cost
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Material: Brass, PVC



Part No.	Color	Wire Range		Dimension mm (inch)			
		sq. mm.	AWG	D	B	L	t
VBT1.25-156	Red	0.5-1.5	22-16	3.6 (0.14)	4.0 (0.16)	21.5 (0.85)	0.4 (0.02)
VBT2-156	Blue	1.5-2.5	16-14	4.4 (0.17)	4.0 (0.16)	22.0 (0.87)	0.4 (0.02)
VBT2-195	Blue	1.5-2.5	16-14	4.4 (0.17)	5.0 (0.20)	22.0 (0.87)	0.4 (0.02)
VBT5.5-156	Yellow	4.0-6.0	12-10	5.4 (0.21)	4.0 (0.16)	25.0 (0.98)	0.4 (0.02)
VBT5.5-195	Yellow	4.0-6.0	12-10	5.4 (0.21)	5.0 (0.20)	25.0 (0.98)	0.4 (0.02)

## VINYL-FULLY INSULATED FEMALE BULLET CONNECTORS

- Disconnect can be inserted and removed from the male bullet without the use of tools for lower installation cost
- Metal insulation grip sleeve crimps to wire insulation, providing protection to the crimp joint during high vibration applications
- Internal wire stop assures proper length of insertion into terminal barrel, providing a higher quality connection
- Material: Brass, PVC



Part No.	Color	Wire Range		Dimension mm (inch)			
		sq. mm.	AWG	D	B	L	t
FVBU1.25-156	Red	0.5-1.5	22-16	3.3 (0.13)	4.7 (0.19)	23.0 (0.91)	0.4 (0.02)
FVBU2-156	Blue	1.5-2.5	16-14	4.0 (0.16)	4.7 (0.19)	23.5 (0.93)	0.4 (0.02)
FVBU2-195	Blue	1.5-2.5	16-14	4.0 (0.16)	4.7 (0.19)	23.5 (0.93)	0.4 (0.02)
FVBU5.5-156	Yellow	4.0-6.0	12-10	6.0 (0.24)	4.7 (0.19)	27.5 (1.08)	0.4 (0.02)
FVBU5.5-195	Yellow	4.0-6.0	12-10	5.3 (0.21)	5.7 (0.22)	23.5 (0.93)	0.4 (0.02)