

**TOOLS**

**TOOLS FOR TERMINALS**



**GIT-516T1**

- For insulated terminals and connectors
- Applicable range: 0.5~6 mm<sup>2</sup> (20-10 AWG)
  - 0.5~1.5 mm<sup>2</sup> (20-16 AWG)
  - 2.5 mm<sup>2</sup> (14 AWG)
  - 4~6 mm<sup>2</sup> (12-10 AWG)
- Length: 230 mm (9.06 inch)
- Weight: 600 g (1.32 lbs)



**GIT-516T2**

- For insulated terminals and connectors
- Applicable range: 10~16 mm<sup>2</sup> (8-6 AWG)
- Length: 230 mm (9.06 inch)
- Weight: 600 g (1.32 lbs)



**GIT-516T3**


- For non-insulated terminals
- Applicable range: 1.5~10 mm<sup>2</sup> (16-8 AWG)
- Length: 230 mm (9.06 inch)
- Weight: 600 g (1.32 lbs)



**GIT-516T4**


- For non-insulated terminals
- Applicable range: 2.5~16 mm<sup>2</sup> (14-6 AWG)
- Length: 230 mm (9.06 inch)
- Weight: 600 g (1.32 lbs)

**TOOLS FOR C SERIES CLOSED-END CRIMP CONNECTORS**



**GIT-517C1**

- Suitable wire range: 0.5~6 mm<sup>2</sup> (20-10 AWG)
- Length: 230 mm (9.06 inch)
- Weight: 600 g (1.32 lbs)



**GIT-517C5**

- Suitable wire range: 4~10 mm<sup>2</sup> (12-8 AWG)
- Length: 230 mm (9.06 inch)
- Weight: 600 g (1.32 lbs)